



Formas construtivas:  
 BP: Bloqueada com tampa passante  
 BC: Bloqueada com tampa cega  
 LP: Livre com tampa passante  
 LC: Livre com tampa cega

Caixa	Diâmetro do eixo		Rolamento	Bucha de fixação (completa)	Dimensões (mm)													Peso (Kg)	
	mm	pol			H	E	A	B	F	L	N	M	P	S	V	C	W		X
SBM 084	35	1.1 / 4"	22208 K	HE 308	60	170	205	60	-	97	46	51	118	1 / 2"	25	26	36	10	3,50
SBM 086		HS 308																	
SBM 08		H 308																	
SBM 097	40	1.7 / 16"	22209 K	HA 309	60	170	205	60	-	106	50	56	122	1 / 2"	25	28	39	10	4,00
SBM 098		HE 309																	
SBM 09		H 309																	
SBM 100	45	1.5 / 8"	22210 K	HS 310	60	170	205	60	-	110	53	57	124	1 / 2"	25	28	39	13	4,30
SBM 101		HA 310																	
SBM 102		HE 310																	
SBM 10		H 310																	
SBM 114	50	1.7 / 8"	22211 K	HS 311	70	210	255	70	-	115	56	59	142	5 / 8"	28	30	41	13	7,00
SBM 115		HA 311																	
SBM 11		H 311																	
SBM 110		HE 311																	
SBM 122	55	2.1 / 8"	22212 K	HS 312	70	210	255	70	-	117	55	62	148	5 / 8"	30	34	45	13	8,00
SBM 12		H 312																	
SBM 133	60	2.3 / 16"	22213 K	HA 313	80	230	275	80	-	120	56	64	162	5 / 8"	30	36	48	13	9,60
SBM 134		HE 313																	
SBM 13		H 313																	
SBM 136		HS 313																	
SBM 157	65	2.7 / 16"	22215 K	HA 315	80	230	280	80	-	128	61	67	168	5 / 8"	30	38	50	13	10,00
SBM 158		HE 315																	
SBM 15		H 315																	
SBM 161	70	2.11 / 16"	22216 K	HA 316	95	260	315	90	-	144	68	76	194	3 / 4"	32	42	55	14	14,00
SBM 162		HE 316																	
SBM 16		H 316																	
SBM 175	75	2.15 / 16"	22217 K	HA 317	95	260	320	90	-	149	70	79	198	3 / 4"	32	44	57	14	14,90
SBM 17		H 317																	
SBM 170		HE 317																	
SBM 18	80	3.3 / 16"	22218 K	H 318	100	290	345	100	-	155	72	83	208	3 / 4"	35	46	59	15	18,00
SBM 183				HA 318															
SBM 184				HE 318															
SBM 194	85	3.1 / 4"	22219 K	HE 319	112	290	345	100	-	162	74	88	224	3 / 4"	35	50	63	16	22,00
SBM 19		H 319																	
SBM 207	90	3.7 / 16"	22220 K	HA 320	112	320	380	110	-	170	77	93	230	7 / 8"	40	54	67	16	22,00
SBM 208		HE 320																	
SBM 20		H 320																	
SBM 221	100	3.11 / 16"	22222 K	HS 322	125	350	410	120	-	180	81	99	258	7 / 8"	45	58	71	16	32,00
SBM 22		H 322																	
SBM 225		HA 322																	
SBM 220		HE 322																	

Caixa	Diâmetro do eixo		Rolamento	Bucha de fixação (completa)	Dimensões (mm)													Peso (Kg)	
	mm	pol			H	E	A	B	F	L	N	M	P	S	V	C	W		X
SBM 243	110	4.3 / 16"	22224 K	HA 3124	140	350	410	120	-	193	89	104	208	7 / 8"	45	60	74	18	37,00
SBM 244		4.1 / 16"		HE 3124															
SBM 24		H 3124																	
SBM 267	115	4.7 / 16"	22226 K	HA 3126	150	380	445	130	-	211	96	115	302	1"	50	64	79	21	46,00
SBM 268		4.1 / 2"		HE 3126															
SBM 26		H 3126																	
SBM 28	125	4.15 / 16" 5"	22228 K	H 3128	150	420	500	150	-	222	101	121	308	1.1 / 4"	50	68	84	21	55,00
SBM 285				HA 3128															
SBM 280				HE 3128															
SBM 303	135	5.3 / 16"	22230 K	HA 3130	160	450	530	160	-	239	112	127	328	1.1 / 4"	60	74	92	21	65,00
SBM 304		5.1 / 4"		HE 3130															
SBM 30		H 3130																	
SBM 327	140	5.7 / 16"	22232 K	HA 3132	170	470	550	160	-	253	117	163	346	1. / 4"	60	76	99	23	76,00
SBM 328		5.1 / 2"		HE 3132															
SBM 32		H 3132																	
SBM 34	150	5.15 / 16" 6"	23134 K	H 3134	170	430	510	180	100	261	118	143	348	1"	70	79	103	23	65,00
SBM 345				HA 3134															
SBM 340				HE 3134															
SBM 367	160	6.7 / 16"	23136 K	HA 3136	180	450	530	190	110	266	120	146	366	1"	75	86	107	23	83,00
SBM 368		6.1 / 2"		HE 3136															
SBM 36		H 3136																	
SBM 38	170	6.3 / 4" 6.15 / 16"	23138 K	H 3138	190	480	560	210	120	279	127	152	388	1"	80	92	113	23	106,00
SBM 382				HE 3138															
SBM 385				HA 3138															
SBM 400	180	7"	23140 K	HE 3140	210	510	610	230	130	291	132	159	422	1.1 / 4"	85	96	118	23	120,00
SBM 40		H 3140																	
SBM 403		7.3 / 16"		HA 3140															
SBM 448	200	7.1 / 2"	23144 K	HE 3144	220	540	640	240	140	309	139	170	448	1.1 / 4"	90	102	124	26	138,00
SBM 44		H 3144																	
SBM 445		7.15 / 16"		HA 3144															
SBM 487	220	8.7 / 16"	23148 K	HA 3148	240	600	700	260	150	328	147	181	490	1.1 / 4"	95	106	136	26	143,00
SBM 488		8.1 / 2"		HE 3148															
SBM 48		H 3148																	
SBM 527	240	9.7 / 16"	23152 K	HA 3152	260	650	770	280	160	346	156	190	530	1.1 / 2"	100	118	146	26	186,00
SBM 52		H 3152																	
SBM 528		9.1 / 2"		HE 3152															
SBM 562	260	9.15 / 16"	23156 K	HA 3156	280	670	790	280	160	345	156	189	560	1.1 / 2"	105	120	149	26	258,00
SBM 560		10"		HE 3156															
SBM 56		H 3156																	
SBM 605	280	10.15 / 16"	23160 K	HA 3160	300	710	830	310	190	379	170	209	609	1.1 / 2"	110	134	155	28	261,00
SBM 600		11"		HE 3160															
SBM 60		H 3160																	
SBM 647	300	11.7 / 16"	23164 K	HA 3164	320	750	880	330	200	424	182	242	645	1.1 / 2"	115	144	190	29	358,00
SBM 648		11.1 / 2"		HE 3164															
SBM 64		H 3164																	
SBM 680	320	12"	23168 K	HE 3168	350	840	1000	350	210	454	196	258	700	1.7 / 8"	120	168	220	32	389,00
SBM 687		12.7 / 16"		HA 3168															
SBM 68		H 3168																	
SBM 725	340	12.15 / 16"	23172 K	HA 3172	360	860	1020	370	220	458	196	262	720	1.7 / 8"	125	172	220	34	540,00
SBM 720		13"		HE 3172															
SBM 72		H 3172																	
SBM 765	360	13.15 / 16"	23176 K	HA 3176	370	880	1040	390	230	464	198	266	740	1.7 / 8"	130	174	225	34	580,00
SBM 760		14"		HE 3176															
SBM 76		H 3176																	